

CONTENTS

中文摘要	i
ABSTRACT.....	iii
CONTENTS.....	v
LIST OF FIGURES	vii
LIST OF TABLES	xi
1. INTRODUCTION	
1.1 Motivation.....	1
1.2 Literature Survey	1
1.3 Contributions of This Dissertation.....	3
1.4 Outline of the Contents	4
2. REVIEW OF A TIME VARYING D_0 CONTROLLED RECTIFIER	
2.1 Introduction.....	6
2.2 Concept of Generalized Zero Voltage Space Vectors.....	6
2.3 Operation Principle	11
3. MODELING OF A CONSTANT D_0 CONTROLLED BOOSTBUCK RECTIFIER	
3.1 Introduction.....	17
3.2 Derivation of Closed Form Duty Ratio Control Laws	17

3.3 Low Frequency DC and AC Models	23
3.4 Some Numerical Simulation Results	29
4. THE PROPOSED MAXIMUM CONSTANT D_0 CONTROL STRATEGY	
4.1 Introduction.....	40
4.2 The Distributed D_0 Control Strategy	41
4.3 Derivation of the Equivalent Circuit Model.....	45
4.4 The Proposed Maximum D_0 Controller	49
4.5 Some Experimental Results	53
5. THE DEAD-BAND CONTROL STRATEGY	
5.1 Introduction.....	64
5.2 The Proposed Dead-Band Control	64
5.3 The Proposed Controller	70
5.4 Some Simulation Results.....	77
6. CONCLUSIONS.....	90
REFERENCES	93

LIST OF FIGURES

Fig. 2.1 Configuration of the conventional three-phase AC/DC rectifier	7
Fig. 2.2 Complete space vectors of terminal voltages on the complex plane	10
Fig. 2.3 Three-phase AC/DC boostbuck rectifier	11
Fig. 2.4 An ideal three-phase input current waveform.....	11
Fig. 3.1 Power circuit of the proposed step up/down AC/DC converter ...	18
Fig. 3.2 Conceptual gating signals of seven switches	20
Fig. 3.3 Waveforms of (a) gating signals of all switches, (b) phase voltage $e_a(t)$ and current $5 i_a$, (c) output voltage $v_o(t)$ under step up operation	31
Fig. 3.4 Waveforms of (a) gating signals of all switches, (b) phase voltage $e_a(t)$ and current $5 i_a$, (c) output voltage $v_o(t)$ under step up operation	33
Fig. 3.5 Bode plots of (a) $T_d(s)$, (b) $T_q(s)$, (c) $T_0(s)$, (d) $T_{em}(s)$ under step up operation.....	37
Fig. 3.6 Bode plots of (a) $T_d(s)$, (b) $T_q(s)$, (c) $T_0(s)$, (d) $T_{em}(s)$ under step down operation.....	39
Fig. 4.1 Power circuit of the bidirectional three phase step-up/down	

converter	41
Fig. 4.2 Gating signal pattern for seven switches	44
Fig. 4.3 Equivalent dc circuit model of the converter	49
Fig. 4.4 Equivalent ac circuit model of the converter	49
Fig. 4.5 An implementation block diagram of the proposed controller	53
Fig. 4.6 Schematic diagram of first switch signal generator (a) Generation for S_1 , S_2 and S_3 signals, (b) Generating of $\frac{1}{2}D_0T_s$	55
Fig. 4.7 Schematic diagram of second switch signal generator (a) Generation for S_4 , S_5 and S_6 signals, (b) Generating of $\frac{1}{2}D_0T_s$	56
Fig. 4.8 The output voltage gain as a function of modulation index d_m and modulation angle \mathbf{j}	56
Fig. 4.9 Measured waveforms of (a) e_a and i_a , (b) V_o and V_c under step down operation.....	58
Fig. 4.10 Measured waveforms of (a) the gating signal of S_7 , (b) inductor current i_L under step down operation.....	60
Fig. 4.11 Measured waveforms of (a) e_a and i_a , (b) V_o and V_c under step up operation.....	61

Fig. 4.12 Measured waveforms of (a) the gating signal of S_7 , (b)	
inductor current i_L	62
Fig. 4.13 Measured waveforms of e_a and i_a under regeneration mode ..	
.....	63
Fig. 5.1 A typical discontinuous duty ratio control pattern for $t \in A$	69
Fig. 5.2 A typical discontinuous duty ratio control pattern for $t \in B$	71
Fig. 5.3 An implementation block diagram of first switch signal generator:	
(a) Generating signal of S_1 , S_2 and S_3 , (b) Illustration of how	
to generate D_0T_s at the proper position for S_1 , S_2 and S_3	75
Fig. 5.4 An implementation block diagram of second switch signal	
generator: (a) Generating signal of S_4 , S_5 and S_6 , (b)	
Illustration of how to generate D_0T_s at the proper position for S_4 ,	
S_5 and S_6	76
Fig. 5.5 An implementation block diagram for the proposed controller	77
Fig. 5.6 Waveforms of (a) $e_a(t)$ and $5i_a(t)$, (b) $v_o(t)$, (c) $v_c(t)$ under	
step down operation	80
Fig. 5.7 Gating signals of the seven active switches under dead-band	
control	80
Fig. 5.8 Simulation waveforms of the step up case (a) $e_a(t)$ and $5i_a(t)$,	

(b) $v_o(t)$, (c) $v_c(t)$	82
-----------------------------------	----

Fig. 5.9 Gating signals of the seven active switches for $V_o = 500\text{ V}$ and

$P_o = 4\text{ kW}$	82
---------------------------	----

Fig. 5.10 Simulation waveforms for step down case $V_o = 48\text{ V}$ (a) $e_a(t)$

and $5i_a(t)$, (b) $v_c(t)$, (c) gating signals of seven active switches

under regeneration mode.....	84
------------------------------	----

Fig. 5.11 Simulation waveforms for step up case $V_o = 500\text{ V}$ (a) $e_a(t)$

and $5i_a(t)$, (b) $v_c(t)$, (c) gating signals of seven active switches

under regeneration mode.....	86
------------------------------	----

Fig. 5.12 Comparison of switching number of one active switch.....87

Fig. 5.13 Duty ratio function of S_1 : (a) $V_o = 48\text{ V}$, rectifier mode, (b)

$V_o = 500\text{ V}$, rectifier mode, (c) $V_o = 48\text{ V}$, regeneration mode, (d)

$V_o = 500\text{ V}$, regeneration mode	89
--	----

LIST OF TABLES

Table 2.1 Possible switch combination status of the six switches	8
Table 2.2 Qualified voltage space vectors.....	10
Table 2.3 The one-boost-mode control strategy of [42]	16
Table 2.4 The two-boost-mode control strategy of [42]	16
Table 5.1 Precise definition of the six intervals	66
Table 5.2 Closed form duty ratio functions of the dead-band case	72