

八.參考文獻

1. R. R. Tummala, "Fundamentals of Microsystems Packaging," McGraw Hill, 2001.
2. W. Zhang, B. Su, Z. Feng, K.C. Gupta and Y.C. Lee, "Study of RF flip-chip assembly with underfill epoxy," Multichip Modules and High Density Packaging Conference, 1998.
3. 咎世蓉, "環保型電子產品的材料趨勢," 經濟部工業局 工安環保報導 2004.8
4. 無鉛焊料合金系與特徵表 巨鋼實業
5. G. Trinite, "PCB fabrication: Achieving solderable finishes," in Proc. Surface Mount Technol. Int. Symp., Aug. 2000.
6. A. Winlow, "Surface finish," solution across the board, 2003.
7. Y. Li, "An Experimental Study On Organic Solderability Preservative," IEEE/CPMT Int'l Electronics Manufacturing Technology Symposium, 1997.
8. M. N. Islam, Y. C. Chan, A. Sharif and M. O. Alam, "Comparative study of the dissolution kinetics of electrolytic Ni and electroless Ni-P by the molten Sn3.5Ag0.5Cu solder alloy," Microelectronics Reliability, Vol. 43, pp. 2031-2037, 2003.
9. M. K. Huang, P. L. Wu and C. Lee, "Effects of different printed circuit board surface finishes on the formation and growth of intermetallics at thermomechanically fatigued small outline J leads/Sn-Pb interfaces," Materials Chemistry and Physics, Vol. 85, pp. 63-67, 2004.
10. S. Canumalla, H. D. Yang, P. Viswanadham and T. O. Reinikainen, "Package to Board Interconnection Shear Strength (PBISS): Effect of Surface Finish, PWB Build-Up Layer and Chip Scale Package Structure," IEEE Transactions on Components and Packaging Technologies , Vol. 27, no. 1, 2004.
11. P. Snugovsky, P. Arrowsmith and M. Romansky, "Electroless Ni/immersion Au interconnects: investigation of black pad in wire bonds and solder joints," J. Electron. Mater., Vol. 30, no. 9, pp. 1262-1270, 2001.
12. S. C. Huang, P. J. Zheng, S. H. Ho, S. C. Lee, H. N. Chen and J. D. Wo, "Board level reliability of PBGA using flex substrate ," Microelectronics Reliability, Vol. 41, pp. 677-687, 2001.

13. J. D. Wu, S. H. Ho, C. Y. Huang, C. C. Liao, P. J. Zheng and S. C. Hung, "Board level reliability of a stacked CSP subjected to cyclic bending," *Microelectronics Reliability*, Vol. 42, pp. 407-416, 2002.
14. H. T. Lee, M. H. Chen, H. M. Jao and T. L. Liao, "Influence of interfacial intermetallic compound on fracture behavior of solder joints," *Materials and Engineering*, Vol. A358, pp. 134-141, 2003.
15. M. Yunus, K. Srihari, J. M. Pitarresi and A. Primavera, "Effect of voids on the reliability of BGA/CSP solder joints," *Microelectronics Reliability*, Vol. 43, pp. 2077-2086, 2003.
16. D. T. Rooney, N. T. Castello, M. Cibulsky, D. Abbott and D. Xie, "Materials characterization of the effect of mechanical bending on area array package interconnects," *Microelectronics Reliability*, Vol. 44, pp. 275-285, 2004.
17. I. Shohji, H. Mori and Y. Orii, "Solder joint reliability evaluation of chip scale package using a modified Coffin-Manson equation," *Microelectronics Reliability*, Vol. 44, pp. 269-274, 2004.
18. V. Horner and H. Balkan, "Flip Chip Technologies Reliability Manual," Issue 3, January, 2001.
19. JEDEC STANDARD- BGA Ball Shear- JESD22-B117.
20. JEDEC STANDARD- Monotonic Bend Characterization of Board-Level Interconnects- IPC/JEDEC-9702 .
21. JEDEC STANDARD- Temperature Cycling - JESD22-A104-B
22. Generic Standard on Printed Board Design- IPC-2221
23. 柯輝耀, "可靠度保證-工程與管理技術之應用," 中華民國品質管理協會, 1997。
24. 陳耀茂, "可靠度工程-方法與應用", 五南圖書出版公司, 2003。
25. M. Meniconi and D.M. Barry, "The PowerFunction Distribution: A Useful And Simple Distribution To Assess Electrical Component Reliability," *Microelectronics Reliability*, Vol. 36, pp. 1207-1212, 1996.
26. 劉國雄, 林樹均, 李勝隆, 鄭晃忠, 葉均蔚, "工程材料科學," 全華科技圖書股份有限公司, 1996。
27. 范嘉偉, "無鉛/錫鉛焊點之金屬間化合物成長機制與潛變特性", 國立清華大學動力機械研究所碩士論文, 2004。

28. AMD Daisy Chain Samples.
29. AN-1112 (Micro SMD Wafer Level Chip Scale Package), National Semiconductor Application Note 1112, August 2000.
30. 陳信文, 陳立宣, 林永森, 陳志銘, “電子構裝技術與材料”, 高立圖書有限公司, 2001。
31. D. R. Flanders, E. G. Jacobs and R. F. Pinizzotto, “Activation Energies of Intermetallic Growth of Sn-Ag Eutectic Solder on Copper Substrates,” Journal Of Electronic Materials, Vol. 26, pp. 883-887, 1997.
32. 白蓉生, “錫料性質對焊接的影響,” PCB 業界動態- 2001年3月報導
33. C. E. Ho, L. C. Shiau and C. R. Kao, “Inhibiting the Formation of $(\text{Au}_{1-x}\text{Ni}_x)\text{Sn}_4$ and Reducing the Consumption of Ni Metallization in Solder Joints,” Journal of Electronic Materials, Vol. 31, No. 11, pp. 1264-1269, 2002.
34. 賴逸少, 黃東鴻, 蔡翰輝, 任明華, “裸晶型晶圓級封裝循環彎曲可靠度實驗與分析,” 中國機械工程學會第二十一屆全國學術研討會論文集, pp. 5861-5866, 2004.
35. W. F. Chen and D. J. Han, “Plasticity for Structural Engineers”, Gau Lih Book Co., 1995.
36. J. A. Bannantine, J. J. Comer and J. L. Handrock, “Fundamentals of Metal Fatigue Analysis”, Prentice-HALL, 1990.
37. ANSYS Release 5.5.1 (1998) ANSYS, Inc., Canonsburg, P. A., U.S.A., 1998.
38. S. Wiese and S. Rzepka, “Time-independent elastic-plastic behaviour of solder materials”, Microelectronics Reliability, Vol. 44, pp. 1893-1900, 2004.
39. R. Ghaffarian, “Qualification approaches and thermal cycle test results for CSP/BGA/FCBGA”, Microelectronics Reliability, Vol. 43, pp. 695-706, 2003.
40. H. L. J. Pang, K. H. Tan, X. Q. Shi and Z. P. Wang, “Microstructure and intermetallic growth effects on shear and fatigue strength of solder joints subjected to thermal cycling aging”, Materials Science and Engineering A, Vol. 307, pp. 42-50, 2001.
41. H. L. J. Pang, T. H. Low, B. S. Xiong, X. Luhua and C. C. Neo, “Thermal cycling aging effects on Sn-Ag-Cu solder joint microstructure, IMC and strength”, Thin Solid Films 462-463, pp. 370-375, 2004.